


# MIS-SERIES

compatible to:

*MIS*<sup>®</sup>  
*SEVEN*<sup>®</sup>



### **PLATFORMS:**



*3,3 mm NP*



*3,75 / 4,2 mm SP*



*5,0 mm WP*



### TITANIUM BASE

incl. screw

MIS 80330000



### SCAN BODY 3D-GUIDE®

for intra + extra oral scanning

MIS 9.S3D3.300



### NT-MILL LAB ANALOG

MIS 5.La3.300



### IMPLANT PICK-UP

for open-tray with integrated screw

MIS TR-00013.3



### ABUTMENT SCREW



Overview of all screwdrivers on pages 344 and 345

MIS 603300



### DIM ANALOG®

MIS 5.DIM.330



**SLEEVE** (belongs to DIM ANALOG)  
plaster model

DIM 5.XSL.A10



compatible to: MIS® / SEVEN®

3,3 mm NP



<b>NT-PREFORM®</b> incl. coloured milling screw	MIS 10.Mi3.300.05	
<b>SCAN BODY 3D-GUIDE®</b> for intra + extra oral scanning	MIS 9.S3D3.300	
<b>NT-MILL LAB ANALOG</b> for NT-Preform®	MIS 5.La3.300	
<b>COLOURED MILLING SCREW</b> for NT-Preform®	MIS 6.Sc3.300	
<b>ABUTMENT SCREW</b>  Overview of all screwdrivers on pages 344 and 345	MIS 603300	
<b>DIM ANALOG®</b>	MIS 5.DIM.330	
<b>SLEEVE</b> (belongs to DIM ANALOG®) plaster model	DIM 5.XSL.A10	
<b>ABUTMENT GRIP</b> for NT-Holder fixture	W 12.100.000	
<b>CUSTOMIZED ABUTMENT</b> milled by NT-iDent  Not available in the USA	TZ15.TiO.Si1	

MIS  
SERIES



### 2-CONNECT®-ABUTMENT SET (STRAIGHT)

incl. 2-CONnect®-Coping and Coping-screw

GH 0,5 mm MIS-2CON 8033001S

GH 2,5 mm MIS-2CON 8033002S



### 2-CONNECT®-ABUTMENT

Male Part

GH 0,5 mm MIS-2CON 8033001M

GH 2,5 mm MIS-2CON 8033002M



### 2-CONNECT®-SCAN BODY 3D-GUIDE®

for intra + extra oral scanning

KS 61 = 1,8 mm

2CON 9.S3D1.800



### 2-CONNECT®-COPING

Female Part

2CON F-U



### COPING-SCREW

Recommended tightening torques: 25 Ncm

KS 61



### 2-CONNECT®-DIM ANALOG®

KS 61 = 1,8 mm

2CON 5.DIM.180



### SLEEVE (belongs to DIM ANALOG®)

plaster model

DIM 5.XSL.A30



### 2-CONNECT®-IMPLANT PICK-UP

integrated screw

KS 61 = 1,8 mm

2CON TR-00021.8



### 2-CONNECT®-LAB ANALOG

KS 61 = 1,8 mm

2CON 5.La1.800





<p><b>2-CONNECT®-ABUTMENT SET (ANGLED)</b> incl. 2-CONnect®-Coping, mounting aid, Coping-screw and Male Part Screw, angled 20°, Gingiva Height 2,5 mm</p>	<p>MIS-2CON 80330A3S</p>	
<p><b>2-CONNECT®-ABUTMENT</b> angled 20°, Gingiva Height 2,5 mm Male Part incl. screw, mounting aid</p>	<p>MIS-2CON 80330A3M</p>	
<p><b>2-CONNECT®-SCAN BODY 3D-GUIDE®</b> for intra + extra oral scanning KS 62 = 1,6 mm</p>	<p>2CON 9.S3D1.600</p>	
<p><b>2-CONNECT®-COPING</b> Female Part</p>	<p>2CON F-U</p>	
<p><b>COPING-SCREW</b> Recommended tightening torques: 15 Ncm</p>	<p>KS 62</p>	
<p><b>MALE PART SCREW</b> for angled 20° 2-CONnect® Abutment Recommended tightening torques: 20 Ncm</p>	<p>MIS 6.Ms3.300</p>	
<p><b>2-CONNECT®-DIM ANALOG®</b> KS 62 = 1,6 mm</p>	<p>2CON 5.DIM.160</p>	
<p><b>SLEEVE</b> (belongs to DIM ANALOG®) plaster model</p>	<p>DIM 5.XSL.A30</p>	
<p><b>2-CONNECT®-IMPLANT PICK-UP</b> integrated screw KS 62 = 1,6 mm</p>	<p>2CON TR-00031.6</p>	
<p><b>2-CONNECT®-LAB ANALOG</b> KS 62 = 1,6 mm</p>	<p>2CON 5.La1.600</p>	



## TITANIUM BASE

incl. screw

MIS 80374200



## SCAN BODY 3D-GUIDE®

for intra + extra oral scanning

MIS 9.S3D3.742



## NT-MILL LAB ANALOG

MIS 5.La3.742



## IMPLANT PICK-UP

for open-tray with integrated screw

MIS TR-00023.7



## ABUTMENT SCREW



Overview of all screwdrivers on pages 344 and 345

MIS 603750



## DIM ANALOG®

MIS 5.DIM.374



**SLEEVE** (belongs to DIM ANALOG)  
plaster model

DIM 5.XSL.A20



compatible to: MIS® / SEVEN®

3,75 / 4,2 mm SP



<b>NT-PREFORM®</b> incl. coloured milling screw	MIS 10.Mi3.742.05	
<b>SCAN BODY 3D-GUIDE®</b> for intra + extra oral scanning	MIS 9.S3D3.742	
<b>NT-MILL LAB ANALOG</b> for NT-Preform®	MIS 5.La3.742	
<b>COLOURED MILLING SCREW</b> for NT-Preform®	MIS 6.Sc3.750	
<b>ABUTMENT SCREW</b>  Overview of all screwdrivers on pages 344 and 345	MIS 603750	
<b>DIM ANALOG®</b>	MIS 5.DIM.374	
<b>SLEEVE</b> (belongs to DIM ANALOG®) plaster model	DIM 5.XSL.A20	
<b>ABUTMENT GRIP</b> for NT-Holder fixture	W 12.200.000	
<b>CUSTOMIZED ABUTMENT</b> milled by NT-iDent  Not available in the USA	TZ15.TiO.Si1	

MIS  
SERIES



### 2-CONNECT®-ABUTMENT SET (STRAIGHT)

incl. 2-CONnect®-Coping and Coping-screw

GH 0,5 mm MIS-2CON 8037421S

GH 2,5 mm MIS-2CON 8037422S



### 2-CONNECT®-ABUTMENT

Male Part

GH 0,5 mm MIS-2CON 8037421M

GH 2,5 mm MIS-2CON 8037422M



### 2-CONNECT®-SCAN BODY 3D-GUIDE®

for intra + extra oral scanning

KS 61 = 1,8 mm

2CON 9.S3D1.800



### 2-CONNECT®-COPING

Female Part

2CON F-U



### COPING-SCREW

Recommended tightening torques: 25 Ncm

KS 61



### 2-CONNECT®-DIM ANALOG®

KS 61 = 1,8 mm

2CON 5.DIM.180



### SLEEVE (belongs to DIM ANALOG®)

plaster model

DIM 5.XSL.A30



### 2-CONNECT®-IMPLANT PICK-UP

integrated screw

KS 61 = 1,8 mm

2CON TR-00021.8



### 2-CONNECT®-LAB ANALOG

KS 61 = 1,8 mm

2CON 5.La1.800



compatible to: MIS® / SEVEN®

3,75 / 4,2 mm SP



<b>2-CONNECT®-ABUTMENT SET (ANGLED)</b> incl. 2-CONnect®-Coping, mounting aid, Coping-screw and Male Part Screw, angled 20°, Gingiva Height 2,5 mm	MIS-2CON 80374A3S	
<b>2-CONNECT®-ABUTMENT</b> angled 20°, Gingiva Height 2,5 mm Male Part incl. screw, mounting aid	MIS-2CON 80374A3M	
<b>2-CONNECT®-SCAN BODY 3D-GUIDE®</b> for intra + extra oral scanning KS 62 = 1,6 mm	2CON 9.S3D1.600	
<b>2-CONNECT®-COPING</b> Female Part	2CON F-U	
<b>COPING-SCREW</b> Recommended tightening torques: 15 Ncm	KS 62	
<b>MALE PART SCREW</b> for angled 20° 2-CONnect® Abutment Recommended tightening torques: 20 Ncm	MIS 6.MS3.750	
<b>2-CONNECT®-DIM ANALOG®</b> KS 62 = 1,6 mm	2CON 5.DIM.160	
<b>SLEEVE</b> (belongs to DIM ANALOG®) plaster model	DIM 5.XSL.A30	
<b>2-CONNECT®-IMPLANT PICK-UP</b> integrated screw KS 62 = 1,6 mm	2CON TR-00031.6	
<b>2-CONNECT®-LAB ANALOG</b> KS 62 = 1,6 mm	2CON 5.La1.600	

MIS  
SERIES

Notice: Products indicated with ® and ™ are registered brand names of the respective manufactures.

**NEXT GENERATION DESIGN – MADE IN GERMANY ///**



## TITANIUM BASE

incl. screw

MIS 80500000



## SCAN BODY 3D-GUIDE®

for intra + extra oral scanning

MIS 9.S3D5.000



## NT-MILL LAB ANALOG

MIS 5.La5.000



## IMPLANT PICK-UP

for open-tray with integrated screw

MIS TR-00035.0



## ABUTMENT SCREW



Overview of all screwdrivers on pages 344 and 345

MIS 603750



## DIM ANALOG®

MIS 5.DIM.500



## SLEEVE (belongs to DIM ANALOG)

plaster model

DIM 5.XSL.A30



compatible to: MIS® / SEVEN®

5,0 mm WP



<b>NT-PREFORM®</b> incl. coloured milling screw	MIS 10.Mi5.000.05	
<b>SCAN BODY 3D-GUIDE®</b> for intra + extra oral scanning	MIS 9.S3D5.000	
<b>NT-MILL LAB ANALOG</b> for NT-Preform®	MIS 5.La5.000	
<b>COLOURED MILLING SCREW</b> for NT-Preform®	MIS 6.Sc3.750	
<b>ABUTMENT SCREW</b>  Overview of all screwdrivers on pages 344 and 345	MIS 603750	
<b>DIM ANALOG®</b>	MIS 5.DIM.500	
<b>SLEEVE</b> (belongs to DIM ANALOG®) plaster model	DIM 5.XSL.A30	
<b>ABUTMENT GRIP</b> for NT-Holder fixture	W 12.300.000	
<b>CUSTOMIZED ABUTMENT</b> milled by NT-iDent  Not available in the USA	TZ15.TiO.Si1	

MIS  
SERIES



### 2-CONNECT®-ABUTMENT SET (STRAIGHT)

incl. 2-CONnect®-Coping and Coping-screw

GH 0,5 mm	MIS-2CON 8050001S
GH 2,5 mm	MIS-2CON 8050002S



### 2-CONNECT®-ABUTMENT

Male Part

GH 0,5 mm	MIS-2CON 8050001M
GH 2,5 mm	MIS-2CON 8050002M



### 2-CONNECT®-SCAN BODY 3D-GUIDE®

for intra + extra oral scanning

KS 61 = 1,8 mm

2CON 9.S3D1.800



### 2-CONNECT®-COPING

Female Part

2CON F-U



### COPING-SCREW

Recommended tightening torques: 25 Ncm

KS 61



### 2-CONNECT®-DIM ANALOG®

KS 61 = 1,8 mm

2CON 5.DIM.180



### SLEEVE (belongs to DIM ANALOG®)

plaster model

DIM 5.XSL.A30



### 2-CONNECT®-IMPLANT PICK-UP

integrated screw

KS 61 = 1,8 mm

2CON TR-00021.8



### 2-CONNECT®-LAB ANALOG

KS 61 = 1,8 mm

2CON 5.La1.800





<p><b>2-CONNECT®-ABUTMENT SET (ANGLED)</b> incl. 2-CONnect®-Coping, mounting aid, Coping-screw and Male Part Screw, angled 20°, Gingiva Height 2,5 mm</p>	<p>MIS-2CON 80500A3S</p>	
<p><b>2-CONNECT®-ABUTMENT</b> angled 20°, Gingiva Height 2,5 mm Male Part incl. screw, mounting aid</p>	<p>MIS-2CON 80500A3M</p>	
<p><b>2-CONNECT®-SCAN BODY 3D-GUIDE®</b> for intra + extra oral scanning KS 62 = 1,6 mm</p>	<p>2CON 9.S3D1.600</p>	
<p><b>2-CONNECT®-COPING</b> Female Part</p>	<p>2CON F-U</p>	
<p><b>COPING-SCREW</b> Recommended tightening torques: 15 Ncm</p>	<p>KS 62</p>	
<p><b>MALE PART SCREW</b> for angled 20° 2-CONnect® Abutment Recommended tightening torques: 20 Ncm</p>	<p>MIS 6.MS3.750</p>	
<p><b>2-CONNECT®-DIM ANALOG®</b> KS 62 = 1,6 mm</p>	<p>2CON 5.DIM.160</p>	
<p><b>SLEEVE</b> (belongs to DIM ANALOG®) plaster model</p>	<p>DIM 5.XSL.A30</p>	
<p><b>2-CONNECT®-IMPLANT PICK-UP</b> integrated screw KS 62 = 1,6 mm</p>	<p>2CON TR-00031.6</p>	
<p><b>2-CONNECT®-LAB ANALOG</b> KS 62 = 1,6 mm</p>	<p>2CON 5.La1.600</p>	