


N-SERIES

compatible to:

*Straumann /
SynOcta®*



PLATFORMS:



3,5 mm NN



4,8 mm RN



6,5 mm WN



TITANIUM BASE

incl. screw

N 800



SCAN BODY 3D-GUIDE®

for intra + extra oral scanning

N 9.S3D3.500



LAB ANALOG

N 50



IMPLANT PICK-UP

for open-tray with integrated screw

N TR-NN013.5



ABUTMENT SCREW



Overview of all screwdrivers on pages 344 and 345

N 60



DIM ANALOG®

N 5.DIM.350



SLEEVE (belongs to DIM ANALOG)

plaster model

DIM 5.XSL.A10





<p>NT-PREFORM® incl. coloured milling screw</p>	<p>GH 0,5 mm GH 1,3 mm</p>	<p>N 10.Mi3.500.05 N 10.Mi3.500</p>	
<p>SCAN BODY 3D-GUIDE® for intra + extra oral scanning</p>		<p>N 9.S3D3.500</p>	
<p>NT-MILL LAB ANALOG for NT-Preform®</p>		<p>N 5.La3.500</p>	
<p>COLOURED MILLING SCREW for NT-Preform®</p>		<p>N 6.Sc3.500</p>	
<p>ABUTMENT SCREW</p>	<p>Overview of all screwdrivers on pages 344 and 345</p>	<p>N 60</p>	
<p>DIM ANALOG®</p>		<p>N 5.DIM.350</p>	
<p>SLEEVE (belongs to DIM ANALOG®) plaster model</p>		<p>DIM 5.XSL.A10</p>	
<p>ABUTMENT GRIP for NT-Holder fixture</p>		<p>W 12.100.000</p>	
<p>CUSTOMIZED ABUTMENT milled by NT-iDent</p>	<p>Not available in the USA</p>	<p>TZ15.TiO.Si1</p>	

N
SERIES



TITANIUM BASE

incl. screw

N 810



SCAN BODY 3D-GUIDE®

for intra + extra oral scanning

N 9.S3D4.800



LAB ANALOG

N 51



IMPLANT PICK-UP

for open-tray with integrated screw

N TR-RN024.8



ABUTMENT SCREW



Overview of all screwdrivers on pages 344 and 345

N 62



DIM ANALOG®

N 5.DIM.480



SLEEVE (belongs to DIM ANALOG)

plaster model

DIM 5.XSL.A20





NT-PREFORM®

incl. coloured milling screw

with shoulder	GH 0,5 mm	N10.Mi4.805.05
with shoulder	GH 1,3 mm	N10.Mi4.805
without shoulder	GH 1,3 mm	N10.Mi 4.800



SCAN BODY 3D-GUIDE®

for intra + extra oral scanning

N 9.S3D4.800



NT-MILL LAB ANALOG

for NT-Preform®

N 5.La4.800



COLOURED MILLING SCREW

for NT-Preform®

N 6.Sc4.865



ABUTMENT SCREW



Overview of all screwdrivers
on pages 344 and 345

N 62



DIM ANALOG®

N 5.DIM.480



SLEEVE (belongs to DIM ANALOG®)

plaster model

DIM 5.XSL.A20



ABUTMENT GRIP

for NT-Holder fixture

W 12.200.000



CUSTOMIZED ABUTMENT

milled by NT-iDent

Not available in the USA

TZ15.TiO.Si1






2-CONNECT®-ABUTMENT SET (STRAIGHT)

incl. 2-CONnect®-Coping and Coping-screw

GH 0,5 mm	N 810 S
GH 2,5 mm	N-2CON 8048002S



2-CONNECT®-ABUTMENT

Male Part

GH 0,5 mm	N 810 M
GH 2,5 mm	N-2CON 8048002M



2-CONNECT®-SCAN BODY 3D-GUIDE®

for intra + extra oral scanning

KS 61 = 1,8 mm

2CON 9.S3D1.800



2-CONNECT®-COPING

Female Part

2CON F-U



COPING-SCREW

Recommended tightening torques: 30 Ncm

KS 61



2-CONNECT®-DIM ANALOG®

KS 61 = 1,8 mm

2CON 5.DIM.180



SLEEVE (belongs to DIM ANALOG®)

plaster model

DIM 5.XSL.A30



2-CONNECT®-IMPLANT PICK-UP

integrated screw

KS 61 = 1,8 mm

2CON TR-00021.8



2-CONNECT®-LAB ANALOG

KS 61 = 1,8 mm

2CON 5.La1.800





<p>2-CONNECT®-ABUTMENT SET (ANGLED) incl. 2-CONnect®-Coping, mounting aid, Coping-screw and Male Part Screw, angled 20°, Gingiva Height 2,5 mm</p>	N-2CON 80480A3S	
<p>2-CONNECT®-ABUTMENT angled 20°, Gingiva Height 2,5 mm Male Part incl. screw, mounting aid</p>	N-2CON 80480A3M	
<p>2-CONNECT®-SCAN BODY 3D-GUIDE® for intra + extra oral scanning KS 62 = 1,6 mm</p>	2CON 9.S3D1.600	
<p>2-CONNECT®-COPING Female Part</p>	2CON F-U	
<p>COPING-SCREW Recommended tightening torques: 15 Ncm</p>	KS 62	
<p>MALE PART SCREW for angled 20° 2-CONnect® Abutment Recommended tightening torques: 20 Ncm</p>	N 6.Ms4.865	
<p>2-CONNECT®-DIM ANALOG® KS 62 = 1,6 mm</p>	2CON 5.DIM.160	
<p>SLEEVE (belongs to DIM ANALOG®) plaster model</p>	DIM 5.XSL.A30	
<p>2-CONNECT®-IMPLANT PICK-UP integrated screw KS 62 = 1,6 mm</p>	2CON TR-00031.6	
<p>2-CONNECT®-LAB ANALOG KS 62 = 1,6 mm</p>	2CON 5.La1.600	



TITANIUM BASE

incl. screw

N 820



SCAN BODY 3D-GUIDE®

for intra + extra oral scanning

N 9.S3D6.500



LAB ANALOG

N 52



IMPLANT PICK-UP

for open-tray with integrated screw

N TR-WN036.5



ABUTMENT SCREW



Overview of all screwdrivers on pages 344 and 345

N 62



DIM ANALOG®

N 5.DIM.650



SLEEVE (belongs to DIM ANALOG)

plaster model

DIM 5.XSL.A30





NT-PREFORM®

incl. coloured milling screw

with shoulder	GH 0,5 mm	N10.Mi6.505.05
with shoulder	GH 1,3 mm	N10.Mi6.505
without shoulder	GH 1,3 mm	N10.Mi 6.500



SCAN BODY 3D-GUIDE®

for intra + extra oral scanning

N 9.S3D6.500



NT-MILL LAB ANALOG

for NT-Preform®

N 5.La6.500



COLOURED MILLING SCREW

for NT-Preform®

N 6.Sc4.865



ABUTMENT SCREW



Overview of all screwdrivers
on pages 344 and 345

N 62



DIM ANALOG®

N 5.DIM.650



SLEEVE (belongs to DIM ANALOG®)

plaster model

DIM 5.XSL.A30



ABUTMENT GRIP

for NT-Holder fixture

W 12.300.000



CUSTOMIZED ABUTMENT

milled by NT-iDent

Not available in the USA

TZ15.TiO.Si1





2-CONNECT®-ABUTMENT SET (STRAIGHT)

incl. 2-CONnect®-Coping and Coping-screw

GH 0,5 mm	N 820 S
GH 2,5 mm	N-2CON 8065002S



2-CONNECT®-ABUTMENT

Male Part

GH 0,5 mm	N 820 M
GH 2,5 mm	N-2CON 8065002M



2-CONNECT®-SCAN BODY 3D-GUIDE®

for intra + extra oral scanning

KS 61 = 1,8 mm

2CON 9.S3D1.800



2-CONNECT®-COPING

Female Part

2CON F-U



COPING-SCREW

Recommended tightening torques: 30 Ncm

KS 61



2-CONNECT®-DIM ANALOG®

KS 61 = 1,8 mm

GH 0,5 mm	2CON 5.DIM.650.05
GH 2,5 mm	2CON 5.DIM.650



SLEEVE (belongs to DIM ANALOG®)

plaster model

DIM 5.XSL.A30



2-CONNECT®-IMPLANT PICK-UP

integrated screw

KS 61 = 1,8 mm

2CON TR-00021.8



2-CONNECT®-LAB ANALOG

KS 61 = 1,8 mm

GH 0,5 mm	2CON 5.La6.500.05
GH 2,5 mm	2CON 5.La6.500





<p>2-CONNECT®-ABUTMENT SET (ANGLED) incl. 2-CONnect®-Coping, mounting aid, Coping-screw and Male Part Screw, angled 20°, Gingiva Height 2,5 mm</p>	N-2CON 80650A3S	
<p>2-CONNECT®-ABUTMENT angled 20°, Gingiva Height 2,5 mm Male Part incl. screw, mounting aid</p>	N-2CON 80650A3M	
<p>2-CONNECT®-SCAN BODY 3D-GUIDE® for intra + extra oral scanning KS 62 = 1,6 mm</p>	2CON 9.S3D1.600	
<p>2-CONNECT®-COPING Female Part</p>	2CON F-U	
<p>COPING-SCREW Recommended tightening torques: 15 Ncm</p>	KS 62	
<p>MALE PART SCREW for angled 20° 2-CONnect® Abutment Recommended tightening torques: 20 Ncm</p>	N 6.Ms4.865	
<p>2-CONNECT®-DIM ANALOG® KS 62 = 1,6 mm</p>	2CON 5.DIM.160	
<p>SLEEVE (belongs to DIM ANALOG®) plaster model</p>	DIM 5.XSL.A30	
<p>2-CONNECT®-IMPLANT PICK-UP integrated screw KS 62 = 1,6 mm</p>	2CON TR-00031.6	
<p>2-CONNECT®-LAB ANALOG KS 62 = 1,6 mm</p>	2CON 5.La1.600	